





**The IP Video Door Phone is an easy and affordable way of door entry communication from entrance over any distance. It is ideal for any door entry communication environment, the virtual office and all IP video communications for business or residential users.**

The IP Helios is an advanced IP video door phone based on SIP standard, competitively priced and easy to use. The IP Helios combines professional design and technology features with excellent picture quality, ease of deployment and broad interoperability with 3rd party SIP products. The IP Helios is the first H.264 IP video door phone that supports real-time high-quality video. 2N solution is unique to the market that includes unique features with easy to use and setup.

- Complete door entry solution
- Voice, video, keypad & access control system in one box
- Modern design
- High quality audio & video
- Remote access



## IP communication:

Communication over IP is provided by the SIP protocol. Video & voice is transmitted via LAN or Internet.



## Code lock:

Directly from the door opening. It is possible to define up to ten global passwords for each of the two switches opening the door. Additionally, it is possible to define one private password for each apartment. Opening period is configurable as well as double door opening delay.



## Card reader:

An installed card reader offers another resource for access to your building. Up to 500 proximity cards or key fobs are available.

If you connect the reader module to your PC, you can check the entries and departures of the individual card holders. If the door is forced, you will receive an alarm announcement.



## Additional switch:

It is intended to be used with the other devices i.e. door locks, barriers, lighting, CCTV, etc. An additional switch is an optional module that can be installed additionally.



## Video:

A connected video camera makes possible visual inspection of those, who are entering building. The picture can be sent either to your PC or Video Phone



## Time scheduling:

Allows you to be reachable at all times. Your entry communication will be transferred according to predefined priorities. Entry Access would be granted based on automatic time scheduling.




## Web based programming:

For easier setting up the parameters, Helios IP has the web based programming interface. You can access the configuration tool from any place in the network and maintain the device remotely.



# How does 2N Helios IP work?

Wireless/Cellular



## Who is the 2N Helios IP door phone intended for?

- Private houses
- Block of flats
- Small & large companies
- Large residential complexes
- Public sector
- Hospitals
- Universities
- Others



# Apartment building

- LAN structure solution
- Video & voice are transferred through data base network
- Comfortable & secure way to see and allow entry to a visitor

Call is transferred to the particular flat via LAN. Reliable solution for a block of flats with data structure. The call from the Helios is accepted on the IP video phone or PC.



# Remote access

- Be reachable at all times
- Opening the door via PC or Smart Phone from any place
- Talk too & see your visitor

Solution for companies with/without receptionist, after hours etc... The receptionist is not at the desk and the SIP based PBX transfers the call to the Smart Phone or remote PC. Call can then be answered and door opened remotely.



# Office

- Communication occurs via LAN network
- Zero costs for calls
- Transfer of voice & video directly to IP video phone or PC


Communication for door entry over IP protocol is performed in a state of art manner. Over IP protocol it is possible not only to communicate with the person standing in front of the entrance, but it is also possible to see and let them enter.

All you need is SIP VoIP phone or PC.



# Basic modules

## With camera




**9137110CE**  
1 button & camera



**9137130CE**  
3 buttons & camera



**9137160CE**  
6 buttons & camera



**9137110CKE**  
1 button & keypad  
& camera



**9137130CKE**  
3 buttons & keypad  
& camera



**9137160CKE**  
6 buttons & keypad  
& camera

## Without camera

**9137110E**  
1 button

**9137130E**  
3 buttons

**9137160E**  
6 buttons

**9137110KE**  
1 button & keypad

**9137130KE**  
3 buttons & keypad

**9137160KE**  
6 buttons & keypad

100 x 210 x 29 mm

## Extenders



**9135181E**  
Extender 8 buttons



**9135182E**  
Extender 16 buttons



**9135310E**  
Infopanel without keypad

100 x 210 x 29 mm

## Vandal resistant protection



**9135511E**  
VR protection 3 buttons,  
masonry fitting



**9135511KE**  
VR protection 3 buttons  
& keypad, masonry fitting



**9135515E**  
VR protection extender  
8 buttons, masonry fitting

Mask: 138,5 x 241 mm, Hole: 110 x 220 x 50 mm

## Roofs & boxes



**9135331E**  
Roof for 1 module



**9135332E**  
Roof for 2 modules



**9135351E**  
Flush fixed box  
for 1 module



**9135352E**  
Flush fixed box  
for 2 modules



**9135361E**  
Roof & box for masonry  
fitting - 1 module



**9135361E**  
Roof & box for masonry  
fitting - 2 modules

103 x 218 x 60 mm

203 x 218 x 60 mm


Mask: 125 x 235 x 46 mm  
Hole: 110 x 220 x 50 mm

Mask: 225 x 235 x 46 mm  
Hole: 210 x 220 x 50 mm

Mask: 129 x 240 x 41 mm  
Hole: 110 x 220 x 50 mm

Mask: 229 x 240 x 41 mm  
Hole: 210 x 220 x 50 mm

## Accessories



**9135311E**  
Infopanel name  
plate




**9135302E**  
Double button  
name plate



**9135301E**  
Name plate



**9137310E**  
Additional switch



**91378900**  
SW Phone




**91378350**  
VoIP Video Phone



**91378100**  
PoE Injectors

## Complementary products

# 2N Helios IP modular system



## Technical parameters:

### 2N Helios IP

<b>Number of buttons</b>	1 to 54 (up to 500)
<b>Interconnection</b>	Direct SIP calls or SIP proxy
<b>Power</b>	PoE (IEEE 802.3 af) or external power supply 12V
<b>Supported protocols</b>	SIP 2.0 (RFC 3261) /TCP/IP/UDP, RTP/HTTP/ARP, ICMP, DHCP, DNS, TFTP, NTP G.711 (A/u-law)
<b>Audio codecs</b>	H.264 baseline real-time video codec (at QCIF, QVGA, CIF or VGA resolution)
<b>Video codecs</b>	up to 30 frames per second



Proudly distributing  
2N Helios in Australia

#### MELBOURNE

Unit 4, 585 Blackburn Rd, Notting Hill 3168, VIC Australia  
 Freecall 1800 817 807  
 Phone +(613) 8562 9000  
 Fax +(613) 8562 9099  
 Email sales@alloy.com.au  
 Web www.alloy.com.au

#### SYDNEY

Address 99 Baxter Rd, Mascot 2020, NSW Australia  
 Freecall 1800 817 807  
 Phone +(612) 8080 9600  
 Fax +(612) 8080 9602  
 Email sales@alloy.com.au  
 Web www.alloy.com.au