

# Ingate SIParator®

*The Ingate SIParator® is a powerful tool that offers enterprises a controlled and secured migration to VoIP (Voice over IP) and other live communications, based on Session Initiation Protocol (SIP). With the SIParator, even the largest of businesses, with branch offices around the world and remote workers, can easily harness the productivity and cost-saving benefits of VoIP and other IP-based communications while maintaining current investments in security technology.*

*Available only from Ingate® Systems, the SIParator works seamlessly with your existing firewall to allow the flow of SIP traffic to reach the user in the enterprise, no matter where he or she is located, as long as there is an Internet connection.*

## Ingate SIParator

While traditional firewalls are not SIP-capable and, therefore, block SIP traffic – including mission-critical applications like VoIP – the SIParator resolves this problem, and enables SIP-based communication to traverse the firewall, while working in tandem with your current security solutions. The Ingate SIParators are available in five different hardware models; 19, 50, 55, 65 and 90.

Ingate SIParators solve the Network Address Translation (NAT) traversal issues inherent in SIP communications, and offer both far- and near-end NAT traversal to extend the SIP capabilities within the corporate network to remote workers. With Ingate products, enterprises can use VoIP and other live communications on the LAN and globally over the Internet or private IP networks. All Ingate SIParators are fully featured, supporting stateful inspection and packet filtering of SIP traffic only. All other protocols are set to default deny to prevent any unwanted intrusion through the SIParator

## Trusted Network Security for VoIP

Ingate's SIP proxy architecture grants fully secure traversal of the SIP traffic. The ports for the media streams are only opened between the specific parties of a call and only for the duration of the call. The SIP proxy inspects the SIP packets before sending them on. TLS and SRTP encryption ensures privacy, making call eavesdropping, call hijacking and call spoofing harder to do. Ingate also supports authentication of users and servers.

## Support for SIP Trunking

More and more Internet telephony service providers offer a SIP trunk – a combined Internet and voice connection. For enterprises using an IP-PBX, SIP trunks are an ideal cost-saving solution as they no longer need local PSTN gateways or costly PRIs/BRIs. The service provider provides the PSTN connection. However, in order for SIP trunks to work, SIP traffic (as well as all other data traffic) must be able to traverse the enterprise firewall. Ingate's SIP Trunking software module, available for all Ingate SIParators, enables firewall and NAT traversal using the built-in SIP proxy, allowing the enterprise to connect to the SIP trunk.

In addition, Ingate SIParators and the Ingate SIP proxy deliver advanced security for all SIP communications, including those *via* a SIP trunk. Ingate products also help ease compatibility issues between the IP-PBX and Internet telephony service provider.

## Choose the Right Features for Your Network

Ingate offers several add-on software modules that allow you to tailor the SIParator to meet the specific demands of your business. Ingate Quality of Service (QoS) sets priorities to different kinds of data and allocates bandwidth for varied purposes – for instance, giving priority to VoIP.

Ingate Remote SIP Connectivity extends the SIP capabilities of the enterprise to employees working remotely (home office workers, road warriors, etc.). Remote SIP Connectivity manages the traversal of the remote NAT from the central Ingate SIParator and also includes a STUN server. Ingate VoIP Survival adds a whole new dimension to hosted VoIP service by securing full redundancy in a SIP-based hosted IP-PBX environment all the way out to the customer premises. It serves as a backup to enhance the reliability and availability of a VoIP application platform. Ingate Advanced SIP Routing provides the ability to fully control and route SIP traffic in an advanced and flexible manner. The module can handle least cost routing, enabling enterprises to make calls globally for local fees.

## Global VoIP Connectivity for your IP-PBX

Ingate SIParators open up a world of possibilities and cost savings when used with a SIP-based IP-PBX. Businesses can not only connect to a SIP trunk, but also route telephone calls via IP, between branch offices, home workers, offices and others using SIP-based VoIP. With an Ingate SIParator, the enterprise is no longer limited to voice; communication can also include video, instant messaging, presence and more.

## Free Software Upgrades for the First Year

Software upgrades for the Ingate SIParators are free for the first year. Thereafter, an annual licensing fee will apply. New software versions can be downloaded quickly and easily online from the Ingate website.


For more information, visit us at [www.ingate.com](http://www.ingate.com) or write to [info@ingate.com](mailto:info@ingate.com).

**inGate®**

[www.ingate.com](http://www.ingate.com)

To learn more about our SIP Firewall and VoIP range **freecall 1800 817 807** or visit [www.voip.alloy.com.au](http://www.voip.alloy.com.au)

Configuration 1: DMZ



Configuration 2: DMZ/LAN



Configuration 3: Standalone



In configuration 2 and 3 the SIParator requires a public IP address.

### Configuration 1: DMZ

The Ingate SIParator connects to the existing firewall through the DMZ interface. All traffic will pass through the existing firewall. This configuration requires that a static range of UDP and TCP ports are opened between the Internet and the SIParator and between the SIParator and the LAN. SIP clients on the LAN need to have the SIParator defined as their outgoing proxy or be referred to it *via* DNS. The firewall continues to control security, but SIP traffic is routed to the LAN only through the SIParator.

### Configuration 2: DMZ/LAN

The Ingate SIParator connects to the DMZ of the existing firewall and to the LAN. This means that SIP traffic and media streams only have to pass through the existing firewall once (or not at all for all calls inside the office). A static range of UDP and TCP ports needs to be opened in the firewall between the Internet and the SIParator. SIP clients on the LAN need to have the SIParator defined as their outgoing proxy or be referred to it *via* DNS.

### Configuration 3: Standalone

The Ingate SIParator connects to both the LAN and the Internet, operating entirely in parallel with the existing firewall. The SIParator will only handle SIP signaling and media streams; everything else will pass through existing firewall. This setup has no requirements for the existing firewall and requires no configuration changes. SIP clients on the LAN need to have the SIParator defined as their outgoing proxy or be referred to it *via* DNS.

## Technical Specifications Ingate SIParators

Feature	Ingate SIParator 19	Ingate SIParator 50	Ingate SIParator 55	Ingate SIParator 65	Ingate SIParator 90
Interfaces (10/100 Mbit/s)	3	0	0	0	0
Interfaces (10/100/1000 Mbit/s)	0	4	4	4	6
Interfaces SFP (mini Gbic)	0	0	0	0	2
Redundant power supply	No	No	No	No	Yes
Flash disc for system operation	Yes	No	No	No	Yes
Dimension WxDxH (mm)	228x146x44	430x369x44	430x369x44	430x369x44	430x485x88
Certifications	CE, FCC, UL	CE, FCC, UL	CE, FCC, UL	CE, FCC, UL	CE, FCC, UL
<b>Management</b>					
Automatic check for new releases	Yes	Yes	Yes	Yes	Yes
Configuration options: Web GUI (HTTP, HTTPS) and CLI (SSH, serial cable)	Yes	Yes	Yes	Yes	Yes
SNMP	Yes	Yes	Yes	Yes	Yes
Max numbers of VLANs	16	32	64	128	256
Internal log to HD	No	Yes	Yes	Yes	Yes
Logging to PCAP file	Yes	Yes	Yes	Yes	Yes
Syslog	Yes	Yes	Yes	Yes	Yes
E-mail events	Yes	Yes	Yes	Yes	Yes
External RADIUS server authentication for GUI and SIP	Yes	Yes	Yes	Yes	Yes
Support for multiple ISPs	Yes	Yes	Yes	Yes	Yes
Free software upgrades	First year	First year	First year	First year	First year
<b>SIP Functionality</b>					
SIP proxy	Yes	Yes	Yes	Yes	Yes
SIP registrar	Yes	Yes	Yes	Yes	Yes
SIP traffic to private IP addresses (NAT/PAT)	Yes	Yes	Yes	Yes	Yes
SRTP (sdescriptions) and Microsoft encrypted RTP	Yes	Yes	Yes	Yes	Yes
TLS encryption	Yes	Yes	Yes	Yes	Yes
SIP Connection set up (SIP + RTP)	0.15 s	0.15 s	0.15 s	0.15 s	0.15 s
RTP data delay (10 Mbps/100 Mbps) network	0.19/0.08 ms	0.19/0.08 ms	0.19/0.08 ms	0.19/0.08 ms	0.19/0.08 ms
Number of concurrent voice RTP sessions (G.711)	40	150	300	650	1500
Concurrent encrypted voice RTP sessions (both SRTP and TLS)	20	75	150	330	750
Busy hour call attempt	36000	72000	79200	79200	234000
Billing and authentication of SIP users from an external RADIUS	Yes	Yes	Yes	Yes	Yes
SIPconnect compliance	Yes	Yes	Yes	Yes	Yes
<b>Add-on modules</b>					
SIP Trunking (connecting an IP-PBX to an ITSPs SIP-trunk)	Yes	Yes	Yes	Yes	Yes
Remote SIP Connectivity (Far-end NAT-passing incl STUN-server)	Yes	Yes	Yes	Yes	Yes
QoS (bandwidth limitation and prioritization)	Yes	Yes	Yes	Yes	Yes
Advanced SIP Routing (flexible routing for SIP traffic)	Yes	Yes	Yes	Yes	Yes
VoIP Survival (VoIP redundancy if Internet connection fails)	Yes	Yes	Yes	Yes	Yes

Ingate 20070501

**inGate**<sup>®</sup>  
www.ingate.com

**ALLOY**<sup>®</sup>

Ingate distributed in Australia by **Alloy Networking and Communications**  
 Freecall **1800 817 807** Fax: 03 9561 7412  
 www.voip.alloy.com.au Email: sales@alloy.com.au