



# RSP126WA / RPS600WA

## Redundant Power Supply



### Specifications of RPS126WA

Physical Ports	
1 redundant power supply port	
Power Delivery	
Max, output power: 126W / 12V per port	
Device Protection	
Thermal Protection Overload Protection	
Mechanical	
Dimensions: TBD Weight: TBD	
Safety	
CSA / NRTL (UL1950,CSA 22.2.9.50) TUV / GS ( EN60950)	
Electromagnetic Compatibility	
CE Mark Class B	
Environmental Specifications	
Temperature: IEC 68-2-14 0 °C to 45 °C (Standard Operating) -40 °C to 70 °C (Non-Operating) Humidity: (Non-condensing) Vibration: IEC 68-2-36, IEC 68-2-6	
Package Content	
1 x RPS126WA 1 x cable 1 x power cord	
Support Devices	
ES3528M-SFP	

### Specification of RPS600WA

Physical Ports	
4 redundant power supply ports	
Power Delivery	
Max, output power: 150W / 12V per port	
Device Protection	
Thermal Protection Overload Protection	
Mechanical	
Dimensions: 440mm x 325mm x 43.95mm (W x D x H) Weight: 7.38kg	
Safety	
CSA / NRTL (UL1950,CSA 22.2.9.50) TUV / GS ( EN60950)	
Electromagnetic Compatibility	
CE Mark Class B FCC Class B VCCI Class B CISPR Class B	
Environmental Specifications	
Temperature: IEC 68-2-14 0 °C to 45 °C (Standard Operating) -40 °C to 70 °C (Non-Operating) Humidity: (Non-condensing) Vibration: IEC 68-2-36, IEC 68-2-6	
Package Content	
1 x RPS600WA 4 x Cable 1 x User Manual 1 x Power Cord 1 x Rack Mount Brackets	
Support Devices	
ES4524D/ ES4548D/ ES5508/ ES3628EA/ ES4626F/ ES4650F/ ECS4610-26T/ ECS4610-50T/ ES3528S	

[www.Edge-Core.com](http://www.Edge-Core.com)