

## *3-Line Business IP Phone for Maximal Office Productivity*

- 132 x 64 graphic LCD, TI Titan chipset
- HD Voice: HD Codec, HD speaker, HD handset
- 3 Programmable keys, 4 Text-Sensitive soft keys
- 2 Ethernet ports, Headset, PoE(802.3af)



Yealink SIP-T22 features intuitive user interface and enhanced functionality which make it easy for people to interact and maximize productivity. With TI leading VoIP voice engine, it enables enhanced high-fidelity audio, outsourced management options, flexible deployment and third-party communications applications. As a cost effective IP solution, it helps users to streamline business processes, delivering a powerful and consistent communications experience for small and large offices environment.

## Network Features

SIP v1(RFC2543), v2(RFC3261)  
 3 User accounts  
 NAT Transverse: STUN mode  
 IP Assignment: Static/DHCP/PPPoE  
 In-Band DTMF, Out-of-Band DTMF, SIP Info  
 Proxy mode and Peer-to-peer SIP link mode  
 TFTP/DHCP/PPPoE client  
 Telnet/HTTP server  
 DNS client  
 NAT/DHCP server  
 Support VLAN, QoS  
 PoE optional

## Voice Features

Wideband Codec: G.722, voice spectrum between 50-7000Hz  
 Narrowband Codecs: G.711, G.726, G.723.1/iLBC, G.729AB and GSM  
 VAD, CNG, AEC, PLC, AJB, AGC  
 Full-duplex hands-free speakerphone

## Telephony Features

Call Hold, Call Waiting, Call Transfer, Call Forward  
 Caller ID, Call List, DND, Redial, Flash  
 3-way Conference, Speed Dial  
 Personal Ring Tone, Voicemail  
 Volume Adjustment, Mute, Speakerphone

## IP PBX System Integration

Dial Plan, Dial-now, Paging  
 Remote/Local XML Phonebook  
 Call Park, Call Pickup, Distinctive Ringtone  
 Auto-answer, intercom

## Config, Upgrade and Usage

Language Customization Support  
 Firmware Upgrade: TFTP/Console/Auto-provision  
 Auto-provision: TR069 Optional  
 Direct IP call without SIP proxy  
 Dial number via SIP server  
 Dial URL via SIP server

## Security

Secure RTP  
 Digest authentication using MD5/MD5-sess  
 Secure configuration file via AES encryption

## Physical Features

TI Titan Chipset  
 LCD: 132x64 with blue backlit  
 3 programmable keys, 4 text-sensitive keys  
 23 hard keys, 2 indication LEDs  
 Headset port: RJ9  
 Network Interface: 2xRJ45 10/100M ports  
 Dimension: 185 X 200 X 90mm  
 Net Weight: 0.77kg  
 Power adapter: Input: AC 100~240V  
 Output: DC 5V/1.2A  
 Operating humidity: 10~95%  
 Storage temperature: up to 60°C

## Package Features

Qty/CTN: 10 PCS  
 N.W/CTN: 22.86KG  
 G.W/CTN: 25.26KG  
 Measurement: 0.073CMB  
 Carton Meas: 565 x 550 x 235MM

## Certifications

