



Overview

The ALLOY AWPS-8T1SFP is a Web Smart 802.3at PoE Gigabit Ethernet switch. With 8x 10/100/1000Base-T RJ-45 copper ports and 1x GbE Copper/(100M/1000M) SFP port and a Switching Capacity of 18Gbps, this high performance Gigabit Ethernet device is ideally suited for smaller networks as their primary switch, or as a departmental switch in larger networks. With the added flexibility of supporting both 100Mbps and 1000Mbps SFP Modules this switch can be integrated quickly and easily into your existing networking infrastructure.

The SFP slots on the switch support all types of Fast Ethernet and Gigabit SFP modules - 100Base-TX Copper or 1000Base-T copper UTP as well as multimode, singlemode and WDM network connectivity over fibre optic cable - enabling copper or fibre uplinks.

With a wide range of web smart management features, the AWPS series is the perfect choice for applications that do not require the full functionality of a SNMP Managed switch. Web Smart features include VLAN's, Port Trunking, STP/RSTP, IGMP Snooping, Port Mirroring, Loop Detection, Broadcast Storm Protection and much more.

Features

- Full-duplex flow control (IEEE802.3x) and half-duplex backpressure
- 8x 10/100/1000Mbps Auto-negotiation Gigabit Ethernet ports
- 1x 100/1000Mbps SFP Fibre port
- IEEE 802.3at/af PoE Support on all 8 Ports
- Jumbo frame support 9KB
- Web smart features provide easy Management, Security, QoS, and Performance
- Up to 30W per port, 130W total PoE Power

Specifications

Performance

Switching Capacity and Forwarding Rate:

Capacity in Millions of Packets per second (mpps) (64-byte packets): 13.39

Switching Capacity in Gigabits per second (Gbps): 18

General

Jumbo Frames: Frame sizes up to 9KB supported on Gigabit interfaces

MAC Table: Up to 8K MAC addresses.

Interface

Ports:

Total Ports: 9 GbE

RJ-45 Ports: 8 GbE

100/1G SFP: 1

Layer 2 Switching

Trunking: Static Trunk (Link Aggregation)

- Up to 4 Groups
- Up to 9 ports per group

Spanning Tree Protocol (STP):

Standard Spanning Tree 802.1d

Rapid Spanning Tree (RSTP) 802.1w

VLAN: Supports up to 16 VLANs

- 802.1Q tag-based VLAN
- Port-based VLAN
- Port Isolation
- Management VLAN

IGMP v1/v2 snooping:

IGMP v1/v2 snooping limits bandwidth-intensive multicast traffic to only the requesters.

Supports 64 multicast groups (source-specific multicasting is also supported)

Port mirroring: Traffic on a port can be mirrored to another port for analysis with a network analyser or RMON probe. Up to N-1 (N is Switch's Ports) can be mirrored to single destination port. A single session is supported.

Loop detection:

Support the loop detection for easy maintenance method to solve network failure problem.

Broadcast Storm Protection:

Prevents traffic on a LAN from being disrupted by a broadcast storm on a port.

Quality of Service

Hardware Priority Queue:

Supports 8 hardware queues

Scheduling:

Strict priority

Queue assignment based on DSCP and class of service (802.1p/ CoS)

Classification:

Port based; 802.1p VLAN priority based; DSCP based; Differentiated Services (DiffServ).

Management

Web GUI interface:

Built-in switch configuration utility for browser-based device configuration (HTTP). Supports configuration, system dashboard, maintenance, and monitoring.

Dual Image:

Dual image provides independent primary and secondary OS files for backup while upgrading.

SNMP: SNMP version 1, 2c with support for traps.

Reset Button:

Provides device reboot and reset to default for recovery and maintenance.

Power over Ethernet (PoE)**IEEE 802.3at PoE delivered over each of the RJ-45 ports within the listed power budgets:**

IEEE 802.3at: Port 1-8

IEEE 802.3af: Port 1-8

Power Dedicated to PoE: 130W Total PoE Power

PoE Port configuration: Supports per Port configuration the PoE function

PoE Scheduling: Supports per Port PoE scheduling to turn on/off the PoE

Environmental

Dimensions: 220 (W)x 44 (H) x 242.4 (D) mm

Weight: 1.98 Kg

Power: 100-240 VAC 50~60 Hz, internal , universal

Operating temperature: 0° to 40° C

Storage temperature: -20° to 70° C

Operating humidity: 10% to 90% , relative, noncondensing

Certification: CE Mark, FCC Part 15 Class A, C-Tick

Alloy Computer Products Australia

Phone: 613 8562 9000

Fax: 613 8562 9099

Address: Unit 4, 585 Blackburn Road
Notting Hill, VIC, 3168
Australia

Mail: P.O. Box 15

Mulgrave, VIC, 3170
Australia

Email: sales@alloy.com.au

<http://www.alloy.com.au/>