



FCR Series Fast Ethernet Media Converters

Dual Purpose Rackmountable or Standalone Fast Ethernet Media Converters

Alloy's FCR series are designed for use either as standalone Fast Ethernet Media Converters, or can be installed as Media converter Modules in an Alloy DCR12 series 12-slot Media Converter Chassis.

The FCR series is one of the most comprehensive Fast Ethernet Converter range available, and comprises of models within three broad technology groups:

- * UTP to Multimode fibre
- * UTP to Singlemode fibre
- * UTP to WDM fibre

Individual models feature media conversion options for RJ-45 to ST, RJ-45 to SC, RJ-45 to LC, RJ-45 to MT-RJ and RJ-45 to VF-45.

A media Converter is used to create network segment over long distances via fibre optic cable, FCR multimode models support up to 2 kilometres range; singlemode and WDM models have a range of up to 100 kilometres.

Our WDM fibre models, which support duplexed TX and RX data over a single fibre core, are often used to minimise the amount of fibre cable required, or where existing fibre cable has reached maximum capacity.

All FCR models provide complete data security through the use of fibre optic cable connectivity.

FCR series converters support Link Failure Pass-through (LFP), ensuring that a LED error status is propagated through a network segment affected by a physical link failure.

All models in the range are housed in a compact, rugged all metal case.

Alloy provides flexible options for powering FCR series Converters. Used in standalone mode, all models in the range can be powered by plugpack, or via an on-board USB port. Optionally,

Converters can be powered by a Self Powering Cable which provides power from the PS/2 keyboard port of a computer or notebook, or by using an Internal Power Adapter Card, which, when installed in a PC, provides power connectivity in a rear slot of the PC to provide power. Use one of these options if you need to use a Converter with a notebook, or don't have a mains power outlet available for a plugpack.



*Alloy FCR100S3.20
WDM Converter*

Alloy Computer Products (Australia) Pty. Ltd.
4/585 Blackburn Rd, Notting Hill, Victoria 3168
T: +61 3 8562 9000 F: +61 3 9561 7412
W: www.alloy.com.au E: alloy@alloy.com.au

Technical Specifications

	UTP to Multimode	UTP to Singlemode	UTP to WDM
Part Numbers	FCR100ST FCR100SC FCR100MT FCR100VF FCR100LC	FCR100SC.05 FCR100SC.20 FCR100SC.40 FCR100SC.60 FCR100SC.80 FCR100SC.100 FCR100SC.2015 FCR100SC.4015 FCR100SC.6015	FCR100S3.20 FCR100S5.20 FCR100S3.40 FCR100S5.40 FCR100S3.60 FCR100S5.60 FCR100S3.80 FCR100S5.80 FCR100S3.100 FCR100S5.100
Speed (Mbps)	100		
Connector Types	TX: RJ-45 FX: ST/SC/MT-RJ/ VF45/LC	TX: RJ-45 FX: SC	TX: RJ-45 FX: SC (single core)
Max. Range.TX (m): FX(Km):	100 2	100 5/20/40/60/80/100	100 20/40/60/80/100
Duplex Mode	TX:/FX Full/Half		
Flow Control	■ Full duplex: 802.3x ■ Half duplex: Backpressure		
Wavelength (nm)	850	Range 5-60Kms: 1310 Range 60Kms>: 1550	S3 models TX:310 RX:1550 S5 models TX:1550 RX:1310
Min. TX Output (dBm)	-19 (all models)	Range 5 Kms: -20 20Kms: -15 40Kms: -8 60Kms: -5 80Kms: -6 100Kms: -6	S3.20/S5.20: -14 S3.40/S5.40: -8 S3.60/S5.60: -5 S3.80: -2 S5.80: -3 S3.100/S5.100: -2
RX Sensitivity (dBm)	-30 (all models)	Range 5 Kms: -32 20Kms: -31 60Kms: -34 80Kms: -34 100Kms: -36	S3.20/S5.20: -31 S3.40/S5.40: -40 S3.60/S5.60: -40 S3.80/S5.80: -35 S3.100/S5.100: -35
Link Fault Pass-through	Yes – Far End Fault (FEF)		
Diagnostic LEDs	■ FX Link/ACT ■ FX FDX/COL ■ TX Link/ACT ■ TX 100 ■ Power		
Power and Install	Standalone: ■ Plugpack ■ USB port ■ Self-powering cable ■ SPA/PCS interface		
Options	Rackmount: ■ DCR12xx Chassis		
Power requirement	1A@+5V DC		
Ambient Temperature	0°C - 50°C		
Humidity	5% - 90%		
Dimensions	26.2(H) x 70.3(W) x 94(D) mm		
Weight:	225 grams		
Compliance	■ FCC Part 15 Class A ■ CE Mark ■ C-Tick		

FCR Fast Ethernet Converter Family - Key features

- ✓ Dual purpose design – use ‘Standalone’ or install Converter Modules in an Alloy DCR12 Media Converter Chassis
- ✓ Ethernet RJ-45 to multimode fibre
- ✓ Ethernet RJ-45 to singlemode fibre
- ✓ Ethernet RJ-45 to WDM fibre – singlemode/singlecore
- ✓ Fibre range – up to 100 kilometres
- ✓ All models with auto-configuring speed/duplex mode, or
- ✓ DIP switches for manual speed/duplex configuration
- ✓ All models support LFP (Link Fault Pass-through)
- ✓ Rugged, compact all metal case
- ✓ Flexible Converter power options, including power via on-board USB port

Wide Range of Ethernet Media Converters

FCR Series includes UTP to multimode, singlemode and WDM fibre models.

Other Alloy Media Converters

FCR Fast Ethernet Converters are part of a wider range of Gigabit Ethernet, Ethernet, ATM, and Serial Comms Media Converters.

Dual Purpose Converters

FCR Series Converters can be used either as standalone devices, or installed in Alloy DCR12 Series 12-slot Media Converter Chassis

Supported Cable Types

FCR Series Converters support RJ-45 for UTP, and ST, SC, LC, MT-RJ or VF-45 fibre connectors, depending on individual model.

Flexible Power Options

All FCR Series Converters are supplied with a plugpack for mains power, or can be powered via an on-board USB port. Alternatively, options are available to power these devices from a PC or SUN computer PS/2 port, or from a PC's internal power supply:

SPC	Self Powering Cable (36cm) for Converters. PC PS/2 connector
SPC-L	Self Powering Cable (71cm) for Converters. PC PS/2 connector
SPC-S	Self Powering Cable (36cm) for Converters. SUN PS/2 connector
SPC-SL	Self Powering Cable (71cm) for Converters. SUN PS/2 connector
SPA-PCS	Internal PC Power Adapter Card & Cables for Converters