



QXE1T1

The QXE1T1 Gateway features 30 channels (E1) or 24 channels (T1) of voice and conforms to a wide variety of signaling protocols. The primary function of this system is to bridge traditional E1 or T1 trunking from the PSTN to a QX IP PBX. Alternatively, it can connect legacy PBXs to the Internet to take advantage of cost-saving SIP trunks. The QXE1T1 has VPN capability and an Auto Attendant for two-stage dialing. Integrating this product with any QX IP PBX allows the Gateway to then be managed through the IP PBX's GUI.



E1/T1 port	1
Ethernet LAN ports	1
Ethernet WAN ports	1
Call Routing capable of modifying caller ID or time of day routing	

FEATURES

Telephony

PBX Features

- Call Detail Records
- Call routing
- Multi-level Auto Attendant with Interactive Voice Response (IVR) and VoiceXMLv2 support
- G3 fax support: T.38 and clear channel fax

Voice Features

Voice Coding:

- G.711, G.726 (16, 24, 32, 40 Kbps), G.729A, iLBC (13,33 kbit/s, 15,2 kbit/s); VAD, CNG, G.168 echo cancellation

VoIP Encryption:

SRTP

VoIP Signaling:

SIP, SIP/TLS

DTMF:

In band & out of band signaling support

VoIP Data and Signaling Protocols

- ITU-T G.711, G.726, G.729 Annex A, G.168-2000, 2002, Q.23, Q.24; IETF RFC 3951- iLBC;
- SIP, SIPS/TLS (RFCs: 2246, 3261, 3263, 3265, 3311, 3323, 3324, 3325, 3428, 3515, 3578, 3581, 3725, 3842, 3856, 3863, 3891, 3892, 4028, 4235)
- SDP (RFC: 2327, 4568)
- RTP/SRTP (RFCs: 1889, 1890, 2833, 3389, 3550, 3551, 3555, 3711, 4733, 3952)
- Fax over IP (ITU-T: T4, T30, T38, V17, V21, V27 ter, V29)

Primary Rate ISDN (PRI) Signaling

- ITU-T: Q.921, Q.931 (DSS1), Q.951; ETSI ETS 300 102 (NET5); ECMA-143-(QSIG); SR-NWT-002120 (NI2); NTT INS1500 for Japan
- PRI switch types: DSS1, NET5, QSIG, 5ESS, NTT INS1500, DMS 100

CAS Signaling

- CAS (MELCAS, ITU, ITU-T2, ITU-T: Q.400, Q.411, Q.421, Q.422, Q.440-Q.442, Q.450-Q.452, Q.454, Q.455, Q.457, Q.458, Q.460-Q.468, Q.470-Q.476;
- Types: E&M Delay Dial, E&M Wink Start, E&M Immediate Start, E&M FGD R2 DTMF, R2 compelled, R2 non-compelled, R2 compelled with ANI, R2 non-compelled with ANI; R2 parameters for Brazil, Mexico etc.)
- ANSI T1.403.02-199, T1.403.02a-2001

Connectivity

Physical Interfaces

Premise connections:

- 1 Ethernet 10/100BASE TX port to connect a PC for configuration purposes (RJ45)

Uplink connections:

- 1 E1/T1 ports to the central office (RJ45)
- 1 Ethernet 10/100BASE TX (RJ45)

System Capacity

- 30 or 24 IP-PSTN calls via E1 or T1 respectively with external parties

Network

- STUN/Network Address Translation (NAT) traversal (RFC 3489)

- IPSec VPN with DES, 3DES and AES encryption in tunnel mode (RFCs: 2402, 2406, 2409)

- Automatic Internet Key Exchange (IKE) keying support

- PPTP VPN, L2TP VPN

- Firewall security via:

- Intrusion Detection System (IDS)
- Network Address Translation (NAT)
- Policy and service-based filtering
- Stateful inspection firewall

- SIP Intrusion Detection System (SIP IDS)

- DHCP server on the LAN side

- DHCP client on the WAN side

- DNS server with forwarding functionality

- Simple Network Time Protocol (SNTP)

- server/client for computer clock synchronization

- PPPoE connection to the ISP with

- PAP/MS CHAP authentication

- IP DIFFSERV for QoS

- SIP tunneling

- Virtual LAN (VLAN/IEEE 802.1Q)

- DNS (DYNDNS) support with third party

- NAT with port forwarding and translation

System

Management

- Operation modes: Master/Slave
- Easy interconnection with QX IP PBXs
- Multilingual web interface accessible from LAN and WAN (HTTP/HTTPS)
- Password control
- User rights management
- Remote diagnostics and software upgrade
- VoIP Carrier Wizard
- Download/restore configuration
- Legible and editable configuration files
- SNMP monitoring and configuration
- Reset button with factory reset option
- Custom Language Pack
- System event notification via SMS/email
- Emergency recovery

Diagnostics/Testing

- System status LED
- E1/T1 and network diagnostics
- Security diagnostics
- Remote testing
- System logs, SIP IDS logs
- Call capture

Billing and Statistics

- Radius Client (RFCs: 2865, 2866), CDRs

Environmental

Physical Dimensions

- Rack-mountable devices:

Measurements:

- 8.0" x 4.0" x 1.6" (20.5 x 10.5 x 4.0 cm)

Weight:

- 1.28 lbs. (580 g)

Conditions

Operating temperature:

- 41°F - 104°F (5°C - 40°C)

Storage temperature:

- 41°F - 140°F (5°C - 60°C)

Non-condensing humidity:

- 5% - 90%

Power Supply

- Input: 85-264VAC, 47-63Hz, AC

- 0.4A/115VAC, 0.2A/230VAC;

- Auxiliary output power: 12.0VDC, 0.6A (max)