

**HUE-411
HUE-411E**

**Industrial 5-port Unmanaged Ethernet Switch With
Fiber Port**



Features

High Performance Network Switching Technology

- ✓ Complies with IEEE 802.3, IEEE 802.3u, IEEE 802.3X
- ✓ Provides 4 x 10/100 Mbps Ethernet ports with RJ-45 connector
- ✓ Provides 1 x 100 Mbps multi-mode SC type fiber port
- ✓ RJ-45 Port support auto MDI/MDI-X crossover
- ✓ Provides broadcast storm protection
- ✓ Supports IEEE 802.3X flow control on full duplex, back pressure on half duplex

Robust Industrial Design

- ✓ Robust Aluminum case complying to IP-31 housing standard
- ✓ Supports operating temperature -10 to 70°C & Extended temperature -40 to 80°C
- ✓ DIN-Rail, panel mounting or desktop installation
- ✓ High level of immunity to electromagnetic interference & power supply surges typically found in industrial plant environments or external curb side enclosures


Reliable Power Design

- ✓ Supports 12 to 48VDC redundant power with polarity reverse protection
- ✓ Wide range redundant power design
- ✓ Equipped with Redundant power inputs
- ✓ Terminal block present for master and slave power

Overview

The Husky HUE-411 series is an Industrial 5-port Unmanaged Ethernet Switch with four 10/100 Mbps Ethernet ports and one multi-mode fiber port. With the optic port, HUE-411 transmits data at high speed for long distances up to 2 km with an SC connector. The entry-level industrial hardened Ethernet switch specifically designed to operate reliably in an electrically harsh, demanding environment, and in hazardous locations. The HUE-411 is equipped with a terminal block to provide dual power inputs with reverse polarity protection. Its IP-31 housing protection, wide operating temperature of -10 to 70°C and DIN-Rail mounting makes HUE-411 suitable for an industrial environment. The E version extends the temperature rating to -40 to 80°C. The HUE-411 is a plug-and-play solution for your Industrial Ethernet applications.

Dimensions



Hardware Specifications

Interface

RJ-45 Ports	4 10/100Base-TX auto-negotiation speed, Full/Half duplex, auto MDI/MDI-X
Fiber ports	1 100Base-FX multi-mode port (SC connector)
LEDs	Per unit: Power x 3 (Green) Per port: Link/Active (Green), Full duplex/Collision (Green)
Power Input	VDC 12-48V Redundant power with polarity reverse protect function and removable terminal block
Power Protection	Power Reverse Polarity: Present
Power Consumption	3.5 watts
Dimensions	IP-31 standard, 54 mm (W) x 135 mm (H) x 105 mm (D)
Installation	DIN-Rail, panel mounting or desktop

Environmental

Operating Temperature	Regular: -10 to 70°C Extended: -40 to 80°C
Storage Temperature	-40 to 85°C (-40 to 185°F)
Operating Humidity	5%~90% RH (Non-condensing)

Technology Specifications

Standard	IEEE 802.3 10Base-T Ethernet IEEE 802.3u 100Base-TX Fast Ethernet IEEE802.3x Flow Control and Back-pressure
Network Media	10Base-T: 2-pair UTP/STP Cat. 3, 4, 5 cable EIA/TIA-568 100-ohm (100m) 100Base-TX: 2-pair UTP/STP Cat. 5/5e cable EIA/TIA-568 100-ohm (100m)
Protocol Technology	CSMA/CD
Switching Architecture	Store and Forward

Performance

Data Transfer Rate	14,880 pps for Ethernet port and 148,800 pps for Fast Ethernet port
MAC Address	1K
Memory Buffer	512 bytes
Back-plane	1.0 Gbps
Transfer packet size	1.19Mpps @ 64bytes

Regulatory Approvals

EMI	FCC Class A
EMS	EN6100-4-2 EN6100-4-3 EN6100-4-4 EN6100-4-5 EN6100-4-6 EN6100-4-8 EN6100-4-11
Safety	UL, cUL, CE/EN60950
Shock	IEC60068-2-27
Vibration	IEC60068-2-6
Free Fall	IEC60068-2-32
Class 1 DIV 2	Pending *
DNV	Pending *
Environmental	WEEE, RoHS
MTBF	325,000 hrs based on Mil-Hdbk-217F, GB
Warranty	5 years

Optical Specifications

Model	Fiber type (um)	Connector	Wavelength (um)	TX Power (min)	TX Power (Max)	Rx Power (Min)	Rx Power (Max)	Link Budget (dbm)	Distance (km)
HUE-411	Multi-mode 62.5/125	SC	1310nm	-19dBm	-14dBm	-31dBm	-14dBm	12dBm	2-3 km
HUE-411-K5	Multi-mode 50/125	SC	1310nm	-20dBm	-14dBm	-34dBm	-14dBm	8dBm	5 km
HUE-411E	Multi-mode 62.5/125	SC	1310nm	-19dBm	-14dBm	-31dBm	-14dBm	12dBm	2-3 km

Ordering Information

HUE-411	Industrial 5-port Unmanaged Ethernet Switch With 1 multi-mode SC fiber port
HUE-411-K5	Industrial 5-port Unmanaged Ethernet Switch with 1 multi-mode port – 5 km
HUE-411E	Industrial 5-port Unmanaged Ethernet Switch with 1 multi-mode port, Extended Temperature -40 to 80°C

*Extended temperature products are produced to order

*Special multi-mode SC type fiber that transmits 5 km distance is produced to order

Recommended Accessories

DR-4524	45W/2A DIN-Rail 24 VDC power supply
DR-7524	75W/3.2A DIN-Rail 24 VDC power supply
DR-120-24	120W/5A DIN-Rail 24 VDC power supply



1800 817 807
sales@alloy.com.au
www.alloy.com.au

Proudly distributed in Australia by

Alloy Computer Products Australia Pty Ltd

Melbourne
 4/585 Blackburn Road
 Notting Hill, VIC 3168
 Tel: (03) 8562 9000
 Fax: (03) 9561 7412

Canberra
 2/42 Geils Court
 Deakin, ACT 2600
 Tel: (02) 6291 4922
 Fax: (02) 6291 8100

Sydney
 99 Baxter Road
 Mascot, NSW 2020
 Tel: (02) 8080 9600
 Fax: (02) 8080 9602