

snom[®] m9

CTI
inside

- DECT 6.0
- Digital audio quality
- 100+ hours of stand-by time
- 4 Concurrent Calls
- 9 Handsets connectivity
- Color Picture Caller-ID
- Voice and call data privacy
- Native IPv6 Support

The **snom** m9 is the next generation snom DECT handheld that empowers users with the convenience of wireless communication along with the widely accepted benefits and feature richness of Voice over IP telephony.

The **snom** m9 delivers excellent speech quality through digital cordless audio. By combining functions of business communication with the ease of use of consumer products, the snom m9 is ideally suited for professional and private use alike. With features such as hands free mode, calling line identification (CLI) by displaying name, number and image of the caller as well as typical mobile phone features such as address book, calendar, calculator and alarm function, the **snom** m9 provides the perfect blend of mobility and accessibility.

The DECT based **snom** m9 provides interference free communication by making use of the dedicated DECT frequency band. In addition, the **snom** m9 delivers the typical benefits of the DECT world such as high

standby time and superior speech quality in addition to internet application integration, thus providing a decisive edge over WLAN-based handhelds.

The access point covers roughly 50m (150 ft) indoors and approx. 300m (1000 ft) outdoors (depending on the actual topology of a building and/or outdoor premise).

The intuitive design of the **snom** m9 makes it a highly consumer friendly and convenient handheld device. With its illuminated keypad and TFT color display, the cordless phone is ideally suited for enterprise and SoHo environments alike. The address book may include JPEG images which are displayed on incoming calls.

The menu driven graphical user interface allows intuitive usage and five navigation keys provide easy access to most of the phone functions saving users from the hassle of searching through complicated menus.

Furthermore, the USB interface and the large flash memory provide an excellent potential for future enhancements. The attractive design underlined by its modern look is what defines this state-of-the-art VoIP wireless telephone.

To enable seamless integration in most VoIP environments, the **snom** m9 delivers pre-configured PBX profiles allowing it to be employed in parallel with the most popular SIP platforms with the click of a button. The **snom** m9 is the first device from snom that comes with full IPv6 support from day one. Such features combined with automatic configuration download make the **snom** m9 a truly unique cordless device. Last but not least, the **snom** m9 incorporates the renowned SIP stack from snom with its decade long proven interoperability and technology leadership.

Technical Data snom m9

DISPLAY

- Color TFT Display (65,536 colors)
- Resolution 128x128 pixel
- 5-step contrast adjustment
- Status indication of signal strength, alarm, "DND", call diversion, battery status, MWI, loudspeaker
- Date & time (manual or auto synchronized)
- Caller ID with name and image
- National Language Support

MEASUREMENTS

- **Size:** 125 x 50 x 20 mm
- **Base station:** 168 x 144 x 32 mm
- **Charging cradle:** 80 x 72 x 21 mm

WEIGHT

- **Handset (approx.):** 98g
- **Base station:** 275g
- **Charging cradle:** 80g

BATTERY

- Li-Ion 3.7V

POWER

- **Charging cradle:** 5.9V DC
- **Base station:** 5V DC

KEYPAD

- Illuminated
- 12 numeric keys
- 2 softkeys
- 5 navigation keys
- Key-barring
- Loudspeaker
- Volume adjustment
- 24-digit input
- Multiple input modes

USER INTERFACE

- Emergency calls
- Call lists (missed, dialed, received)
- Address book (500 entries)

- Digital clock with automatic time synchronization
- Talktime indication
- Convenient and intuitive menu structure
- Polyphonic ringtones
- Handsfree mode
- Customizable wallpaper
- Screensaver
- Auto answer

FURTHER FUNCTIONS

- USB interface
- Music-on-hold (only when connected to PBX)
- Call hold
- Call transfer
- Call redirection
- Caller lists
- Call Waiting Indication (CWI)
- Message Waiting Indication (MWI)
- Do Not Disturb (DND)
- RSS Feed Reader
- Missed calls indication
- 4 simultaneous VoIP calls
- Registration of up to 9 handsets
- Intercom (handset-to-handset calling without PBX)
- Calling line identification from address book
- Mailbox (PBX)
- VCARD 3.0 support
- Speed dial
- LDAP
- CLIP/CLIR
- Dial plans
- SIP URI Dialing

AUDIO

- Wideband audio
- Voice Encryption (SRTP)
- Mute function
- Volume adjustment – 6 steps
- Separate settings for a) handsfree and b) headset
- Ringer volume – 6 steps + OFF

- 2.5 mm Headset Jack
- Multiple advisory tones
- Acoustic warning for low battery status and charging

CODECS

- G.711, G.722, G.726, G.729

VOIP

- Pre-configured PBX profiles
- IPv6 ready
- RFC3261-compliant
- Digest and NTLM authentication
- DNS SRV (RFC3263),
- Offer/answer (RFC3264)
- Indication of incoming messages (MWI in accordance with RFC3265)
- DTMF (Inband, Outband, SIP INFO)
- SIP configuration via base station or handset
- SIPS and SRTP Support
- STUN support for NAT Traversal

INSTALLATION

- Automatic software updates
- Automatic upload of settings via HTTP
- Control LEDs on base station for network activity, power and VoIP registration
- Reset key
- VLAN
- **Standards:** DECT/DECT 6.0, GAP
- **Supports:** DECT encryption
- Device diagnostics mode
- LLDP

CONFIGURATION

- Embedded web server
- Autoconfiguration via HTTP/HTTPS
- Embedded X.509 certificate
- Over-the-air and USB firmware upgrade



1800 817 807

www.alloy.com.au
sales@alloy.com.au

Proudly distributed in Australia by
Alloy Computer Products Pty Ltd

Melbourne
4/585 Blackburn Road, Notting Hill, VIC 3168
Tel: (03) 85629000 Fax: (03) 8562 9099

Sydney
Suite 204, Milsons Landing, 6A Glen Street,
Milsons Point, NSW, 2061
Tel: (02) 8080 9600 Fax: (03) 8562 9099

snom technology AG

Charlottenstraße 68–71
10117 Berlin, Germany
tel: +49 30 39833-0
fax: +49 30 39833-111
sip: info@snom.com
mail: info@snom.com