

3-Line Business IP Phone for Maximal Office Productivity

- 132 x 64 graphic LCD, TI Titan chipset
- HD Voice: HD Codec, HD speaker, HD handset
- 3 Programmable keys, 4 Text-Sensitive soft keys
- 2 Ethernet ports, Headset, PoE(802.3af)



Yealink SIP-T22 features intuitive user interface and enhanced functionality which make it easy for people to interact and maximize productivity. With TI leading VoIP voice engine, it enables enhanced high-fidelity audio, outsourced management options, flexible deployment and third-party communications applications. As a cost effective IP solution, it helps users to streamline business processes, delivering a powerful and consistent communications experience for small and large offices environment.

Network Features

SIP v1(RFC2543), v2(RFC3261)
3 User accounts
NAT Transverse: STUN mode
IP Assignment: Static/DHCP/PPPoE
In-Band DTMF, Out-of-Band DTMF, SIP Info
Proxy mode and Peer-to-peer SIP link mode
TFTP/DHCP/PPPoE client
Telnet/HTTP server
DNS client
NAT/DHCP server
Support VLAN, QoS
PoE optional

Voice Features

Wideband Codec: G.722, voice spectrum between 50-7000Hz
Narrowband Codecs: G.711, G.726, G.723.1/iLBC, G.729AB and GSM
VAD, CNG, AEC, PLC, AJB, AGC
Full-duplex hands-free speakerphone

Telephony Features

Call Hold, Call Waiting, Call Transfer, Call Forward
Caller ID, Call List, DND, Redial, Flash
3-way Conference, Speed Dial
Personal Ring Tone, Voicemail
Volume Adjustment, Mute, Speakerphone

IP PBX System Integration

Dial Plan, Dial-now, Paging
Remote/Local XML Phonebook
Call Park, Call Pickup, Distinctive Ringtone
Auto-answer, intercom

Config, Upgrade and Usage

Language Customization Support
Firmware Upgrade: TFTP/Console/Auto-provision
Auto-provision: TR069 Optional
Direct IP call without SIP proxy
Dial number via SIP server
Dial URL via SIP server

Security

Secure RTP
Digest authentication using MD5/MD5-sess
Secure configuration file via AES encryption

Physical Features

TI Titan Chipset
LCD: 132x64 with blue backlit
3 programmable keys, 4 text-sensitive keys
23 hard keys, 2 indication LEDs
Headset port: RJ9
Network Interface: 2xRJ45 10/100M ports
Dimension:185 X 200 X 90mm
Net Weight:0.77kg
Power adapter: Input: AC 100~240V
Output: DC 5V/1.2A
Operating humidity: 10~95%
Storage temperature: up to 60°C

Package Features

Qty/CTN: 10 PCS
N.W/CTN:22.86KG
G.W/CTN:25.26KG
Measurement: 0.073CMB
Carton Meas: 565 x 550 x 235MM

Certifications

